

New Installation

New Installing the DOOR for ORACLE or Eloquence

New Installing on MPE/iX 6.5 without Turbo Store

Please request for DAT tape media and follow the steps:

```
:File T=DRINSTAL;Dev=tape
:Restore *T;@.@@;CREATE;SHOW=SHORT
```

New Installing on MPE/iX 7.0 or 7.5

1. Log on as system manager:

```
: HELLO MANAGER.SYS
```

2. Use Reflection File Transfer function to upload the file "DOORINST" to HP3000 using the LABEL format

3. Restore the tape as follows:

```
:File T=DRINSTAL;Dev=disc
:Restore *T;@.@@;CREATE;SHOW=SHORT
```

4. After the file has been restored, execute the command file

```
:DOORINST.PUB.IMAXSOFT
```

This sets the proper security for the account and groups.

DOOR account structure:

1. Account access security required:
(R,X:ANY;W,A,L:AC)
2. Account capability required:
AM,AL,GL,ND,SF,BA,IA,MR,DS,PH,PM
3. PUB group access security required:
(R,X:ANY;W,A,L,S:AC)
4. PUB group capability required:
BA,IA,MR,DS,PH,PM

If you plan to initiate DOOR's interceptor and shooter processes outside the DOOR account, then you must set:

```
DOOR account:      ACCESS=(R,X,W,A,L:ANY)
CONFIG.DOOR group: ACCESS=(R,X,W,A,L,S:ANY)
```

Upgrade

Upgrading the DOOR for ORACLE or Eloquence

Upgrading on MPE/iX 6.5 without Turbo Store

Please request for DAT tape media and follow the steps:

```
:File T=DRUPGRAD;Dev=tape  
:Restore *T;@.@@;CREATE;SHOW=SHORT
```

Upgrading on MPE/iX 7.0 or 7.5

1. Log on as system manager:

```
: HELLO MANAGER.SYS
```

2. Use Reflection File Transfer function to upload the file "DRUPGRAD" to HP3000 using the LABEL format

3. Restore the tape as follows:

```
:File T=DRUPGRAD;Dev=disc  
:Restore *T;@.@@;CREATE;SHOW=SHORT
```

New Installing on HP-UX

1. "Root" authority is necessary to restore the server files with correct attributes.
2. Use FTP BINARY to transfer the DEPOT file into the directory "/tmp"
3. Issues the command

<code>swinstall -s /tmp/otbora.depot OPENTURBO</code>	for ORACLE
<code>swinstall -s /tmp/otbelo.depot OPENTURBO</code>	for Eloquence

Upgrading on HP-UX

1. "Root" authority is necessary to restore the server files with correct attributes.
2. Use FTP BINARY to transfer the DEPOT file into the directory "/tmp"
4. Issues the command

<code>swinstall -s /tmp/otbora_upgrade.depot OPENTURBO</code>	for ORACLE
<code>swinstall -s /tmp/otbelo_upgrade.depot OPENTURBO</code>	for Eloquence

Special Instructions:

Extra steps for installing ELOQUENCE OPENTURBO and DOOR:

You need to be sure that the library libelo3k.sl is point to the proper Eloquence IMAGE library:

The default symbolic link for libelo3k.sl is:

```
$cd /opt/imaxsoft/openturbo3.7/eloquence/lib
$ll libelo3k.sl
lrwxrwxr-x  1 root      sys          41 Jan 23 11:39 libelo3k.sl ->
/opt/eloquence6/lib/pa11_32/libimage3k.sl
```

If the default link points to an incorrect file, use following command to reset the symbolic link for pointing to Eloquence IMAGE library that is installed on your system:

```
$cd /opt/imaxsoft/openturbo3.7/eloquence/lib
$rm libelo3k.sl
$ln -s /opt/eloquence6/lib/pa20_32/libimage3k.sl libelo3k.sl
```